

ROLL LABEL - Vinyls

Issue date : 05/01/2005
Date last modification : 09/12/2016**4-RL3B-00241 RI-167/80 PVC MATT WHITE AP900 WG62****Face Material**

Matt white soft vinyl.

Type	Soft vinyl
Colour and Finish	Matt white
Weight	110 g/m ² ±10% ISO-536
Thickness	80 µ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP900
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Very High
Tack	6 N/25mm FINAT FTM9
Final Adhesion	9 N/25mm FINAT FTM2

This adhesive complies with FDA 175.105.

Liner

Type	One side siliconised Glassine
Colour and Finish	White
Weight	62 g/m ² ±10% PP-032 - ISO 536
Thickness	54 µ ±10% ISO 534
Transparency	>45 % DIN 53 147-64

Applications

Promotional and general uses labels.

Printing Methods

Printing methods: letterpress UV, screenprinting UV, gravure, flexo UV and hot stamping.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

