

GRAPHICS - Thermal Transfer Printable papers

Issue date : 14/06/2010
Date last modification : 21/08/2018**4-GL2B-06452 RI-6480 ANTIGRAFFITI UV SCREEN PROTECTED CLEAR AP906
EXTRA PERMANENT PLUS PET30****Face Material**

Gloss clear LH polyester.

Type	LH Polyester	
Colour and Finish	Gloss Clear	
Weight	28 g/m ² ±10%	ISO-536
Thickness	20 µ ±10%	ISO 534-80

Adhesive

Extra permanent acrylic adhesive with excellent performance even at extreme outdoor conditions, and with very high UV protection characteristics.

Reference	AP906 extra permanent	
Type	Acrylic extra permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-40°C/+140°C	
Shear	Very high	
Tack	15 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

Liner

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	42 g/m ² ±10%	PP-032 - ISO 536
Thickness	30 µ ±10%	ISO 534
Transparency	>95 %	DIN 53 147-64

Applications

Offers extreme high clarity, very high UV resistance and also has excellent anti-graffiti properties, indicated for lamination on rough surface and UV ink-jet printing,

Printing MethodsNot printable.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

