

**GRAPHICS** - Mounting FilmsIssue date : 05/01/2005  
Date last modification : 30/04/2018**4-GL2B-02626 MONOTAPE 950P CLEAR AP905 PERMANENT/AP905 PERMANENT WKPE120****Adhesive**

Solvent based permanent acrylic adhesive featuring good water and high UV resistance. Designed for overlamination and mounting applications.

Reference	AP905 permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+120°C
Shear	Medium
Tack	Medium N/inch <sup>2</sup>
Final Adhesion	High N/inch

**Face Material**

Self wound construction based on a clear polyester carrier.

Type	Polyester
Colour and Finish	Clear
Weight	17 g/m <sup>2</sup> ±10% ISO-536
Thickness	12 µ ±10% ISO 534-80

**Adhesive**

Solvent based permanent acrylic adhesive featuring good water and high UV resistance. Designed for overlamination and mounting applications.

Reference	AP905 permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+120°C
Shear	Medium
Tack	Medium N/inch <sup>2</sup>
Final Adhesion	High N/inch

**Liner**

Type	Two side silicone coated two side PE coated Kraft
Colour and Finish	White
Weight	120 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	140 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

**Applications**

For photographic and digital mounting.

**Printing Methods**

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

