

**GRAPHICS** - Mounting Films

 Issue date : 05/01/2005  
 Date last modification : 30/04/2018

**4-GL2B-03273 ULTRACRYSTALLINE CLEAR AR866 REMOVABLE/AP906 PERMANENT PET30**
**Liner**

|                   |                                |                  |
|-------------------|--------------------------------|------------------|
| Type              | One side siliconised polyester |                  |
| Colour and Finish | Clear                          |                  |
| Weight            | 42 g/m <sup>2</sup> ±10%       | PP-032 - ISO 536 |
| Thickness         | 30 µ ±10%                      | ISO 534          |
| Transparency      | >95 %                          | DIN 53 147-64    |

**Adhesive**

Solvent based removable adhesive featuring low adhesion and easy and clean removability from plastics and metallic substrates.

|                  |                         |
|------------------|-------------------------|
| Reference        | AR866 removable         |
| Type             | Acrylic removable       |
| Min. Appl. Temp. | +10°C                   |
| Service Temp.    | -20°C/+100°C            |
| Shear            | High                    |
| Tack             | Low N/inch <sup>2</sup> |
| Final Adhesion   | Low N/inch              |

**Face Material**

Double side adhesive construction based on a clear polypropylene carrier.

|                   |                          |            |
|-------------------|--------------------------|------------|
| Type              | Polypropylene            |            |
| Colour and Finish | Clear                    |            |
| Weight            | 27 g/m <sup>2</sup> ±10% | ISO-536    |
| Thickness         | 30 µ ±10%                | ISO 534-80 |

**Adhesive**

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

|                  |                          |
|------------------|--------------------------|
| Reference        | AP906 permanent          |
| Type             | Acrylic permanent        |
| Min. Appl. Temp. | +10°C                    |
| Service Temp.    | -20°C/+140°C             |
| Shear            | Very high                |
| Tack             | High N/inch <sup>2</sup> |
| Final Adhesion   | Very high N/inch         |

**Liner**

|                   |                                |                  |
|-------------------|--------------------------------|------------------|
| Type              | One side siliconised polyester |                  |
| Colour and Finish | Clear                          |                  |
| Weight            | 42 g/m <sup>2</sup> ±10%       | PP-032 - ISO 536 |
| Thickness         | 30 µ ±10%                      | ISO 534          |
| Transparency      | >95 %                          | DIN 53 147-64    |

**Applications**

Ultraclear mounting films with two clear filmic liners suitable for 'optically clear' applications.

**Printing Methods**

Not printable.  
 Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

