

ROLL LABEL - Static Cling FilmsIssue date : 05/01/2005
Date last modification : 09/12/2016**4-RL2C-01071 RI-488/110 PO GLOSS CLEAR PP60****Face Material**

Gloss clear chlorine free static cling polyolefine.

Type	Static cling polyolefine	
Colour and Finish	Gloss clear	
Weight	90 g/m ² ±10%	ISO-536
Thickness	110 μ ±10%	ISO 534-80

Adhesive

This material is without adhesive.

Reference	n.a.	
Type	n.a.	
Min. Appl. Temp.	n.a.	
Service Temp.	n.a.	
Shear	n.a.	
Tack	n.a. N/25mm	FINAT FTM9
Final Adhesion	n.a. N/25mm	FINAT FTM2

Liner

Type	Polypropylene	
Colour and Finish	White	
Weight	55 g/m ² ±10%	PP-032 - ISO 536
Thickness	60 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Ecological removable labels for windows, glasses and plate glass objects.. During converting of the material the temperature must not be higher than 45°C. For storage follow the recommended storage conditions.

Printing Methods

The film requires corona treatment for printing with letterpress UV, screenprinting UV and gravure. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

