

**GRAPHICS** - Soft Vinyls

 Issue date : 05/01/2005  
 Date last modification : 13/12/2016

**4-GL3B-00106 RI-205/80 PVC GLOSS CLEAR AP902 WK135**
**Face Material**

Gloss clear soft vinyl.

Type	Soft vinyl	
Colour and Finish	Gloss clear	
Weight	104 g/m <sup>2</sup> ±10%	ISO-536
Thickness	80 μ ±10%	ISO 534-80

**Adhesive**

Acrylic permanent adhesive featuring good clarity. Excellent adhesion on a wide variety of materials, including apolar substrates (like PE and PP). This adhesive can be used on slightly rough surfaces.

Reference	AP902	
Type	Acrylic permanent	
Min. Appl. Temp.	+5°C	
Service Temp.	-20°C/+100°C	
Shear	Medium	
Tack	11 N/25mm	FINAT FTM9
Final Adhesion	10 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

**Liner**

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	145 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Promotional labels, big size window stickers and electrowelded pouches.

**Printing Methods**

Printable with solvent based and UV screenprinting, offset UV.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

