

GRAPHICS - Soft Vinyls

Issue date : 12/11/2008  
Date last modification : 13/12/2016**4-GL3B-02045 RI-205/100 PVC GLOSS CLEAR AR801 WK135****Face Material**

Gloss clear soft vinyl.

Type	Soft vinyl	
Colour and Finish	Gloss clear	
Weight	130 g/m <sup>2</sup> ±10%	ISO-536
Thickness	100 μ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive featuring good clarity and clean removability from glass, laminated plastics and crosslinked enamels. Not suitable for application on papers, PVC and air dried paints and varnishes.

Reference	AR801	
Type	Acrylic removable	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+120°C	
Shear	High	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

**Liner**

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	145 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Promotional labels, big size window stickers and electrowelded pouches.

**Printing Methods**

Printable with solvent based and UV screenprinting, offset UV.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24  
20867 Caponago (MB) ITALY  
e-mail: info@ritrama.com  
www.ritrama.com