

GRAPHICS - Security Range

 Issue date : 05/01/2005
 Date last modification : 13/12/2016

4-GL2B-00606 RI-630/36 PET GLOSS SILVER CHAIN TC AP901 WKPE144
Face Material

Bright silver top coated polyester that contains on the underside an invisible security release pattern. When label is applied and an attempt of removal is made pattern separates from the film and remains on the applied surface.

Type	Top coated polyester	
Colour and Finish	Bright silver metallised	
Weight	50 g/m ² ±10%	ISO-536
Thickness	36 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901	
Type	Acrylic permanent	
Min. Appl. Temp.	-5°C	
Service Temp.	-40°C/+120°C	
Shear	High	
Tack	8 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	Siliconised two side PE Kraft	
Colour and Finish	White	
Weight	144 g/m ² ±10%	PP-032 - ISO 536
Thickness	155 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Tamperproof labels. Available also in "chain" pattern .

Printing Methods

Printing methods: UV screenprinting.
 Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS:**

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

