

Technical Data Sheet

Issue date: 05/01/2005 Date last modification: 13/12/2016

# **GRAPHICS** - Rigid Vinyls

# 4-GL3B-01356 RI-210/80 PVC GLOSS SILVER TC AP906-40 WKPE144

#### Face Material

Top coated gloss silver metallised rigid vinyl.

Type Top coated rigid vinyl Colour and Finish Gloss silver

ISO-536 Weight 105 g/m<sup>2</sup> ±10% ISO 534-80 Thickness 80 µ ±10%

## Adhesive

Acrylic permanent adhesive featuring very good ultimate adhesion and excellent cohesion even at high temperatures. Not recommended on apolar substrates (like PE and PP).

Reference AP906-40

Acrylic permanent Type

Min. Appl. Temp. +10°C -40°C/+140°C Service Temp. Very high Shear

FINAT FTM9 Tack 15 N/25mm Final Adhesion FINAT FTM2 7 N/25mm

## Liner

Siliconised two side PE Kraft

Colour and Finish White

Weight 144 g/m<sup>2</sup> PP-032 - ISO

536 ±10%

155 µ ±10% ISO 534 **Thickness** DIN 53 147-64 Transparency n.a. %

### **Applications**

Promotional and decorative labels, specifically developed for doming.

#### **Printing Methods**

Suitable for UV and solvent based screenprinting and UV offset printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

## Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of  $22^{\circ}C \pm 2^{\circ}C$  and 50  $\pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



