

ROLL LABEL - Specialties

Issue date : 05/01/2005
Date last modification : 12/07/2018**4-RL2F-03636 PO IRID RED/GREEN+RI-787/55 PP CLEAR AP901 WG62****Face Material**

Iridescent film laminated with a clear bi-oriented polypropylene, that confers to the material a special visual effect.

Thickness	66 μ \pm 10%	ISO 534-80
Type	Iridescent film laminated with BOPP	
Colour and Finish	Red/Green	
Weight	65 g/m ² \pm 10%	ISO- 536

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901
Type	Acrylic permanent
Min. Appl. Temp.	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	8 N/25mm FINAT FTM9
Final Adhesion	7 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine
Colour and Finish	White
Weight	62 g/m ² \pm 10% PP-032 - ISO 536
Thickness	54 μ \pm 10% ISO 534
Transparency	>45 % DIN 53 147-64

Applications

Flexible and conformable labels, for the cosmetics, personal and home care industries.

Printing Methods

It must be Corona treated before printing with letterpress UV, flexo UV e gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C \pm 2°C and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

