

GRAPHICS - RI-WRAP

Issue date : 05/01/2005
Date last modification : 13/12/2016**4-GL2B-07436 RI-ECLIPSE WINDOW 20 ASP PERMANENT PET25****Face Material**

Light grey tinted gloss clear polyester.

| | | |
|---|-------------------------------|------------|
| Type | Polyester | |
| Colour and Finish | Light grey tinted gloss clear | |
| Weight | 55 g/m ² ±10% | ISO-536 |
| Thickness | 40 µ ±10% | ISO 534-80 |
| Outdoor vertical exposure durability* | 48 | |
| Outdoor horizontal exposure durability* | 18 | |

Adhesive

Acrylic permanent adhesive featuring high shear and adhesion even at high temperatures. Good adhesion on a wide variety of surfaces, except for apolar substrates (like PE and PP). Ideal for car windows applications.

| | | |
|------------------|-------------------|------------|
| Reference | ASP | |
| Type | Acrylic permanent | |
| Min. Appl. Temp. | +5°C | |
| Service Temp. | -30°C/+140°C | |
| Shear | Very high | |
| Tack | Medium N/25mm | FINAT FTM9 |
| Final Adhesion | High N/25mm | FINAT FTM2 |

Liner

| | | |
|-------------------|--------------------------------|------------------|
| Type | One side siliconised polyester | |
| Colour and Finish | Clear | |
| Weight | 32 g/m ² ±10% | PP-032 - ISO 536 |
| Thickness | 25 µ ±10% | ISO 534 |
| Transparency | >95 % | DIN 53 147-64 |

Applications

Installation-friendly tinted film specific for car windows, that excel both in outdoor performance and good looks. This is the least shaded film of the series proposed by Ritrama.

Certified by Kraftfahrt-Bundesamt ABG number D 5535 dated 19.02.2010.

This film is available in 1.00 m wide roll.

Printing Methods

Application: only wet application.

All surfaces to which the material will be applied must be thoroughly cleaned with good quality cleaning solutions.

This film as a rule is not printed.

Users must check their own national regulations covering this subject before they apply these products to any vehicle.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

