

**ROLL LABEL** - Seal & Reseal Range

Issue date : 20/09/2007  
Date last modification : 12/12/2016

## 4-RL2D-03853 RI-707/60 PP GLOSS CLEAR TC AR806 WG62

### Face Material

Gloss clear top coated polypropylene.

Type	Top coated polypropylene	
Colour and Finish	Gloss clear	
Weight	54 g/m <sup>2</sup> ±10%	ISO-536
Thickness	60 μ ±10%	ISO 534-80

### Adhesive

Acrylic semi-permanent adhesive featuring high resistance to moisture. Soft peel adhesion, suitable for seal and reseal labels on wet packed products (like baby or cosmetic wipes). Suitable for short term outdoor applications.

Reference	AR806	
Type	Acrylic removable	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+100°C	
Shear	High	
Tack	9 N/25mm	FINAT FTM9
Final Adhesion	5 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

### Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	54 μ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

### Applications

Seal and reseal labels for wet packed products like baby wipes, cosmetics and household products. Prior to its use it is necessary to check compatibility between the adhesive and the content of the packages. Specific for PP flow-wrap surfaces.

Not recommended for fan folder tags.

### Printing Methods

Printable with letterpress UV, screenprinting UV, flexo UV, gravure and hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24  
20867 Caponago (MB) ITALY  
e-mail: info@ritrama.com  
www.ritrama.com

