

**ROLL LABEL** - SEAL AND RESEALIssue date : 01/07/2015  
Date last modification : 12/12/2016**4-RL2D-08816 RI-707/60 PP GLOSS CLEAR TC AR841 WG62****Face Material**

Gloss clear top coated polypropylene.

Type	Top coated polypropylene	
Colour and Finish	Gloss clear	
Weight	54 g/m <sup>2</sup> ±10%	ISO-536
Thickness	60 µ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive featuring soft peel adhesion. Suitable for seal &amp; reseal labels on dry packed products made with polar surface.

Reference	AR 841	
Type	Modified Acrylic	
Min. Appl. Temp.	+ 5°	
Service Temp.	-40° / +120°	
Shear	High	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	54 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

For open-close labels on dry polar plastic packagings, for a "no-label look" effect. Prior testing is always necessary to assess the behaviour of the adhesive on the particular application surface.

**Printing Methods**

Printing methods: UV letterpress, UV screenprinting, flexo UV, gravure and hot stamping. It is recommended to overvarnish in order to improve the scratch and chemical resistance of the finished label.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

