

**ROLL LABEL - SEAL AND RESEAL**Issue date : 05/06/2012  
Date last modification : 06/02/2018**4-RL2D-07375 RI-707/60 PP GLOSS WHITE TC AR827B WG62****Face Material**

Gloss white top coated polypropylene.

Type	Top coated polypropylene	
Colour and Finish	Gloss white	
Weight	54 g/m <sup>2</sup> ±10%	ISO-536
Thickness	60 μ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive featuring high resistance to moisture. Soft peel adhesion, suitable for seal and reseal labels on wet packed products (like baby or cosmetic wipes). APEO free.

Reference	AR827B	
Type	Acrylic removable	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+100°C	
Shear	High	
Tack	6 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	54 μ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

Seal and reseal labels for wet packed products like baby wipes, cosmetics and household products. Prior to its use it is necessary to check compatibility between the adhesive and the content of the packages, and between the adhesive and the substrate.

Not recommended for fan folder tags.

**Printing Methods**

Printing methods: UV letterpress, UV screenprinting, flexo UV, gravure and hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

