

ROLL LABEL - Seal & Reseal RangeIssue date : 29/08/2011
Date last modification : 26/06/2018**4-RL2D-07139 RI-707/120 PP GLOSS CLEAR TC AR827B WG62****Face Material**

Gloss clear top coated polypropylene.

Type	Polypropylene top coated		
Colour and Finish	Gloss clear		
Weight	110 g/m ² ±10%	ISO-536	
Thickness	120 µ ±10%	ISO 534-80	

Adhesive

Acrylic removable adhesive featuring high resistance to moisture. Soft peel adhesion, suitable for seal and reseal labels on wet packed products (like baby or cosmetic wipes). APEO free.

Reference	AR827B		
Type	Acrylic removable		
Min. Appl. Temp.	+10°C		
Service Temp.	-30°C/+100°C		
Shear	High		
Tack	6 N/25mm	FINAT FTM9	
Final Adhesion	2 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised Glassine		
Colour and Finish	White		
Weight	62 g/m ² ±10%	PP-032 - ISO 536	
Thickness	54 µ ±10%	ISO 534	
Transparency	>45 %	DIN 53 147-64	

Applications

Seal and reseal labels, where a very stiff label is needed, for wet packed products like baby wipes, cosmetics and household products or for dry food like dried fruit or coffee. Prior to its use it is necessary to check compatibility between the adhesive and the content of the packages, and between the adhesive and the substrate. Not recommended for fan folder tags.

Printing Methods

Printable with UV letterpress, UV screenprinting, flexo UV, gravure and hot stamping. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

