

ROLL LABEL - Security Range

Issue date : 05/01/2005
Date last modification : 12/12/2016**4-RL1C-01688 STAMP SEMIGLOSS AP969 WK100BP****Face Material**

Woodfree white medium-glossy coated paper

Type	Coated paper	
Colour and Finish	White	
Weight	80 g/m ² ±10%	ISO-536
Thickness	65 µ ±10%	ISO 534

Adhesive

Acrylic adhesive permanent, water removable .

Reference	AP 969
Type	Permanent acrylic
Min. Appl. Temp.	+ 5 °C
Service Temp.	-40°C / + 100 °C
Shear	Medium
Tack	High N/inch ²
Final Adhesion	High N/inch

Liner

Type	One side siliconised, coated paper	
Colour and Finish	White	
Weight	100 g/m ² ±10%	PP-032 - ISO 536
Thickness	86 µ ±10%	ISO 534

Applications

Typical applications: for stamps, philatelic uses .
The stamp could be easily removed from the envelopes by soaking in the water without residues left on the backing.

Printing Methods

Suitable for different printing methods : letterpress, flexo, offset and gravure.
Printable on the back of release paper.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

