

ROLL LABEL - WINE LABELSIssue date : 07/05/2015
Date last modification : 18/02/2019**4-RL1C-08667 LAID WHITE WS AP1300 WG74 FSC® CERTIFIED****Face Material**

Smooth natural laid white wet strength paper. FSC® certified.

Type	Smooth natural paper	
Colour and Finish	White	
Weight	90 g/m ² ±10%	ISO-536
Thickness	110 μ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive , especially recommended for wine bottles.

Reference	AP1300	
Type	Acrylic, permanent	
Min. Appl. Temp.	+ 5°C	
Service Temp.	- 40°C/+120°C	
Shear	High	
Tack	9 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	72 g/m ² ±10%	PP-032 - ISO 536
Thickness	63 μ ±10%	ISO 534
Transparency	>40 %	DIN 53 147-64

Applications

High quality labels for beverages, wine and promotional uses.
Excellent water resistance with good stability after immersion in ice and water.
For neck labels and small diameter bottles, tests are recommended for the intended application.
The performance of the material on non perfectly cylindrical containers must be validated for the specific product application.
REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with letterpress UV, flexo UV, offset UV and gravure.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

