

ROLL LABEL - WINE LABELSIssue date : 14/05/2015
Date last modification : 20/03/2018**4-RL1C-08701 TELA WS RP1003 WG74 FSC® CERTIFIED****Face Material**

Coated embossed line white wet strength paper. FSC® certified.

Type	Coated embossed line paper		
Colour and Finish	White		
Weight	90 g/m ² ±10%	ISO-536	
Thickness	105 μ ±10%	ISO 534-80	

Adhesive

Rubber based permanent adhesive featuring good adhesion on slightly wet surfaces.

Reference	RP1003		
Type	Rubber permanent		
Min. Appl. Temp.	0°C		
Service Temp.	-20°C/+70°C		
Shear	Very High		
Tack	14 N/25mm	FINAT FTM9	
Final Adhesion	11 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.

Liner

Type	One side siliconised Glassine		
Colour and Finish	White		
Weight	72 g/m ² ±10%	PP-032 - ISO 536	
Thickness	63 μ ±10%	ISO 534	
Transparency	>40 %	DIN 53 147-64	

Applications

High quality labels for beverages, wine and promotional uses.
REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with letterpress UV, flexo UV, offset UV and gravure.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

