

ROLL LABEL - TIREIssue date : 05/05/2008
Date last modification : 14/12/2016**4-RL2D-02827 RI-754/60 PP TYRE WHITE TC RP2001 WG74DS****Face Material**

White top coated cavitated polypropylene.

Type	Top coated PP film	
Colour and Finish	White	
Weight	45 g/m ² ±10%	ISO-536
Thickness	60 μ ±10%	ISO 534-80

Adhesive

Rubber based permanent adhesive (high grammage) with high tack and adhesion on rough and apolar (like PE and PP) substrates. Specifically designed for tyre applications.

Reference	RP2001	
Type	Rubber permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+40°C	
Shear	Very high	
Tack	25 N/25mm	FINAT FTM9
Final Adhesion	18 N/25mm	FINAT FTM2

Liner

Type	Double side siliconised Glassine	
Colour and Finish	White	
Weight	72 g/m ² ±10%	PP-032 - ISO 536
Thickness	63 μ ±10%	ISO 534
Transparency	>40 %	DIN 53 147-64

ApplicationsSpecifically developed for tyre labeling. High quality labels for critical surfaces.
Not recommended for fan folder tags.**Printing Methods**

Printable with offset UV, flexo UV, letterpress UV and thermal transfer.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life18 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

