

ROLL LABEL - WINE LABELS

 Issue date : 15/05/2015
 Date last modification : 13/06/2018

4-RL1B-08726 CAST GLOSS WS BARRIER AP1300 WG74 FSC® CERTIFIED
Face Material

Cast Coated wet strength paper. Special "Barrier" construction. FSC® certified.

| | | |
|-------------------|---------------------------|------------|
| Type | Cast Coated paper | |
| Colour and Finish | White | |
| Weight | 105 g/m ² ±10% | ISO-536 |
| Thickness | 110 μ ±10% | ISO 534-80 |

Adhesive

Acrylic permanent adhesive featuring good clarity. and water resistance.

| | | |
|------------------|-------------------|------------|
| Reference | AP 1300 | |
| Type | Acrylic permanent | |
| Min. Appl. Temp. | + 5°C | |
| Service Temp. | - 40°C/ + 170°C | |
| Shear | High | |
| Tack | 9 N/25mm | FINAT FTM9 |
| Final Adhesion | 7 N/25mm | FINAT FTM2 |

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV .

Liner

| | | |
|-------------------|-------------------------------|------------------|
| Type | One side siliconised Glassine | |
| Colour and Finish | White | |
| Weight | 72 g/m ² ±10% | PP-032 - ISO 536 |
| Thickness | 63 μ ±10% | ISO 534 |
| Transparency | >40 % | DIN 53 147-64 |

Applications

For production of high quality labels for beverages and wine . Excellent water resistance with good performances after immersion in ice-water. Not suggested for bottle neck labels.

REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with UV letterpress, UV, screenprinting, UV flexo, UV offset and hot foil.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

