

ROLL LABEL - WINE LABELS

 Issue date : 15/05/2015
 Date last modification : 13/06/2018

4-RL1F-08728 SPECCHIO BARRIER AP1300 WG74 FSC® CERTIFIED
Face Material

Vacuum metallised paper silver finishing, lacquered for printing. Special "Barrier" construction. FSC® certified.

Type	Metallised paper	
Colour and Finish	Silver	
Weight	108 g/m ² ±10%	ISO-536
Thickness	95 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring good clarity and water resistance.

Reference	AP 1300	
Type	Acrylic permanent	
Min. Appl. Temp.	+ 5° C	
Service Temp.	- 40°C / + 170 °C	
Shear	High	
Tack	9 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV .

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	72 g/m ² ±10%	PP-032 - ISO 536
Thickness	63 µ ±10%	ISO 534
Transparency	> 40 %	DIN 53 147-64

Applications

High quality labels for beverages, wine and promotional uses. Excellent water resistance with good stability after immersion in ice and water. Not suggested for bottle neck labels.

REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with lettepress UV, offset UV and flexo. It is recommended that the printed surface is sealed/overvarnished to minimise scuffing.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

