

INDUSTRIAL - INDUSTRIAL

Issue date : 23/09/2010
Date last modification : 13/12/2016**4-IL2B-01286 MONOTAPE 2530 CLEAR AP902/AP902****Adhesive**

The adhesive on both sides of the PET film is permanent acrylic with very high initial tack.

Reference	AP 902
Type	Acrylic permanent
Min. Appl. Temp.	+5°C
Service Temp.	-20°C/+100°C
Shear	Medium
Tack	11 N/25mm FINAT FTM9
Final Adhesion	10 N/25mm FINAT FTM2

Face Material

Double sided adhesive coated polyester selfwound.

Type	Polyester
Colour and Finish	Clear
Weight	17 g/m ² ±10% ISO-536
Thickness	12 µ ±10% ISO 534-80

Adhesive

Reference	AP 902
Type	Acrylic permanent
Min. Appl. Temp.	+5°C
Service Temp.	-20°C/+100°C
Shear	Medium
Tack	11 N/25mm FINAT FTM9
Final Adhesion	10 N/25mm FINAT FTM2

Liner

Type	Double side siliconised glasine
Colour and Finish	White
Weight	90 g/m ² ±10% PP-032 - ISO 536
Thickness	87 µ ±10% ISO 534

Applications

For laminating and making self adhesive products e.g. wickets, nameplates etc.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS:**

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

