

ROLL LABEL - Polyesters

Issue date : 05/01/2005  
Date last modification : 13/12/2016**4-RL2B-02359 RI-609/50 PET GLOSS CLEAR ASP29 WHITE PET50****Face Material**

Clear top coated polyester.

Type	Top coated polyester	
Colour and Finish	Gloss clear	
Weight	52 g/m <sup>2</sup> ±10%	ISO-536
Thickness	36 µ ±10%	ISO 534-80

**Adhesive**

White pigmented (opaque) silicone adhesive.

Reference	ASP29 WHITE	
Type	white pigmented (opaque) silicone adhesive	
Min. Appl. Temp.	-10°C	
Service Temp.	-40°C/+150°C	
Shear	Excellent	
Tack	15 N/inch <sup>2</sup>	
Final Adhesion	13 N/inch	

**Liner**

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	70 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	50 µ ±10%	ISO 534
Transparency	>95 %	DIN 53 147-64

**Applications**

Designed for use on air bags or other very low energy surfaces, such as silicone release surfaces or untreated polyolefine films.

**Printing Methods**Printable with traditional printing methods.  
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
All information is subject to change without prior notice.

