

ROLL LABEL - COMMODITY

Issue date : 02/04/2015  
Date last modification : 18/10/2018**4-RL1B-08616 COATED 80 RP3000 YG60 FSC® CERTIFIED****Face Material**

Medium gloss white coated woodfree paper. FSC® certified.

Type	Coated paper
Colour and Finish	White
Weight	80 g/m <sup>2</sup> ±10% ISO-536
Thickness	65 µ ±10% ISO 534-80

**Adhesive**

Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates. RP3000 adhesive combines the rubber based properties with high speed conversion

Reference	RP3000
Type	Rubber permanent
Min. Appl. Temp.	+5°C
Service Temp.	-30°C / +80°C
Shear	Very High
Tack	18 N/25mm FINAT FTM9
Final Adhesion	8 N/25mm FINAT FTM2

**Liner**

Type	One side siliconised Glassine
Colour and Finish	Yellow
Weight	57 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	51 µ ±10% ISO 534
Transparency	>50 % DIN 53 147-64

**Applications**

Blank and logistic labels.

**Printing Methods**

Printable with letterpress UV, flexo UV, offset UV, gravure and thermal transfer with selected ribbons.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

