

**ROLL LABEL** - Uncoated PapersIssue date : 05/01/2005  
Date last modification : 18/10/2018**4-RL1C-01671 FORMS RP1001 YG60****Face Material**

White smooth woodfree paper.

Type	Smooth paper
Colour and Finish	White
Weight	70 g/m <sup>2</sup> ±10% ISO-536
Thickness	78 µ ±10% ISO 534-80

**Adhesive**

Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates.

Reference	RP1001
Type	Rubber permanent
Min. Appl. Temp.	0°C
Service Temp.	-10°C/+70°C
Shear	Very High
Tack	16 N/25mm FINAT FTM9
Final Adhesion	9 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry &amp; moist, non fatty foodstuffs) according to the German Recommendations XIV.

**Liner**

Type	One side siliconised Glassine
Colour and Finish	Yellow
Weight	57 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	51 µ ±10% ISO 534
Transparency	>50 % DIN 53 147-64

**Applications**

For EDP labels.

**Printing Methods**

Printable with letterpress UV and with EDP and laser printers.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

