

GRAPHICS - INK-JET DIGITAL

Issue date : 29/04/2009
Date last modification : 30/04/2018**4-GL2B-09284 RI-JET 675 ECO S/L PRINT GLOSS CLEAR AR807 REMOVABLE PET30****Face Material**

Gloss clear polyester.

Type	Polyester	
Colour and Finish	Gloss clear	
Weight	105 g/m ² ±10%	ISO-536
Thickness	75 µ ±10%	ISO 534-80

Adhesive

Removable adhesive with medium tack and good repositionability.

Reference	AR807 removable
Type	Acrylic Removable
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+100°C
Shear	Medium
Tack	5 N/inch ²
Final Adhesion	4 N/inch

Liner

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	42 g/m ² ±10%	PP-032 - ISO 536
Thickness	30 µ ±10%	ISO 534
Transparency	>95 %	DIN 53 147-64

ApplicationsFor advertising and promotional applications (window graphics, outdoor and indoor posters, billboards and signs).
Non recommended for application on steel.**Printing Methods**

Material printable with Latex and solvent and eco-solvent technology.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

