

ROLL LABEL - POLITEX

 Issue date : 17/05/2017
 Date last modification : 03/08/2017

4-RL2D-09875 - POLYTEX FILMIC GLOSS CLEAR ER WG90 PTD GREEN
Face Material

Gloss clear top coated Polytex for direct garment labelling - delicate fabrics

Type	Polytex filmic	
Colour and Finish	Gloss clear	
Weight	45 g/m ² ±10%	ISO-536
Thickness	50 μ ±10%	ISO 534-80

Adhesive

Fabric friendly adhesive designed to cleanly remove without damaging the garment - pre-testing recommended.

Reference	ER	
Type	Fabric Friendly Adhesive	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+120°C	
Shear	Very high	
Tack	Low N/25mm	FINAT FTM9

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	90 g/m ² ±10%	PP-032 - ISO 536
Thickness	77 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Garment labelling - we recommend pre-testing of garment prior to labelling. We offer a free of charge testing service, please call to discuss.

Printing Methods

Printable by UV letterpress, UV screen, gravure and hot stamping. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

 24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

