

ROLL LABEL - POLITEX

Issue date : 17/05/2017
Date last modification : 03/08/2017**4-RL2L-09315 - POLYTEX FILMIC GLOSS WHITE ER WG90 PTD GREEN****Face Material**

Gloss white top coated Polytex for direct garment labelling - delicate fabrics.

Type	Polytex film		
Colour and Finish	Gloss white		
Weight	48 g/m ² ±10%	ISO-536	
Thickness	50 µ ±10%	ISO 534-80	

Adhesive

Fabric friendly adhesive designed to cleanly remove without damaging the garment - pre-testing recommended.

Reference	ER		
Type	Fabric Friendly Adhesive		
Min. Appl. Temp.	+5°C		
Service Temp.	-40°C/+120°C		
Shear	Very high		
Tack	Low N/25mm	FINAT	FTM9

Liner

Type	One side siliconised Glassine		
Colour and Finish	White		
Weight	90 g/m ² ±10%	PP-032 - ISO 536	
Thickness	77 µ ±10%	ISO 534	
Transparency	n.a. %	DIN 53 147-64	

Applications

Garment labelling - we recommend pre-testing of garment prior to labelling. We offer a free of charge testing service, please call to discuss.

Printing Methods

Printable by UV letterpress, UV screen, gravure and hot stamping.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

