

ROLL LABEL - POLITEX

Issue date : 22/12/2008
Date last modification : 03/08/2017**4-RL1B-04361 POLYTEX PAPER RI-AF WG62 PTD BLUE****Face Material**

Semi-gloss white paper.

Type	Semi-gloss paper	
Colour and Finish	Gloss white	
Weight	80 g/m ² ±10%	ISO-536
Thickness	75 µ ±10%	ISO 534-80

Adhesive

Fabric friendly adhesive designed to cleanly remove without damaging the garment - pre-testing recommended.

Reference	RI-AF
Type	fabric friendly adhesive
Min. Appl. Temp.	+5°C
Service Temp.	-30°C / +120°C
Shear	Medium
Tack	High N/inch ²

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	PP-032 - ISO 536
Thickness	55 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Garment labelling - we recommend pre-testing of garment prior to labelling. We offer a free of charge testing service, please call to discuss.

Printing Methods

Printable with letterpress UV, UV screen, gravure and hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

