

ROLL LABEL - POLITEX

Issue date : 17/05/2017  
Date last modification : 03/08/2017**4-RL2L-09350 - POLYTEX FILMIC GLOSS WHITE XP WG 90 PTD RED****Face Material**

Gloss white top coated Polytex for direct garment labelling - fibrous fabrics.

Type	Top coated polypropylene	
Colour and Finish	Gloss white	
Weight	48 g/m <sup>2</sup> ±10%	ISO-536
Thickness	50 µ ±10%	ISO 534-80

**Adhesive**

Fabric friendly adhesive designed to cleanly remove without the damaging the garment - pre-testing recommended.

Reference	XP	
Type	Fabric friendly	
Min. Appl. Temp.	-5°C	
Service Temp.	-25°C/+120°C	
Shear	Medium	
Tack	Very high N/25mm FINAT FTM9	

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	90 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	77 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Garment labelling - we recommend pre-testing of garment prior to labelling. We offer a free of charge testing service, please call to discuss.

**Printing Methods**

Printable with letterpress UV, UV screen, gravure and hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

