

ROLL LABEL - POLITEX

 Issue date : 17/05/2017
 Date last modification : 03/08/2017

4-RL2D-09870 - GLOBALWARE FILMIC GLOSS CLEAR REMOVABLE WG62
Face Material

Gloss white filmic grade designed for high gloss, high strength removable labelstock.

Type	Globalware film	
Colour and Finish	Gloss clear	
Weight	45 g/m ² ±10%	ISO-536
Thickness	50 µ ±10%	ISO 534-80

Adhesive

Removable adhesive designed to give good adhesion and clean removal from wide range of smooth finish homeware items.

Reference	Removable	
Type	Acrylic removable	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+120°C	
Shear	High	
Tack	Low N/25mm	FINAT FTM9

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	PP-032 - ISO 536
Thickness	54 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Excellent adhesion/removability on smooth surfaces homeware products, such as glass, ceramics, painted surfaces, PET, plastics. etc
 We always recommend pre-testing of the suitability to the substrate

Printing Methods

Printable with UV letterpress, UV flexo, UV offset and gravure.
 Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
 All information is subject to change without prior notice.

