

ROLL LABEL - POLITEX

Issue date : 17/05/2017  
Date last modification : 03/08/2017**4-RL2D-09856 - GLOBALWARE FILMIC GLOSS WHITE SEMI-REMOVABLE WG62****Face Material**

Gloss white filmic grade designed for high gloss, high strength removable labelstock.

Type	Globalware film	
Colour and Finish	Gloss white	
Weight	48 g/m <sup>2</sup> ±10%	ISO-536
Thickness	50 µ ±10%	ISO 534-80

**Adhesive**

Semi-removable grade giving good adhesion/removability to wide range of smooth and textured finishes.

Reference	Semi-removable	
Type	Acrylic removable	
Min. Appl. Temp.	+10°C	
Service Temp.	-40°C/+100°C	
Shear	High	
Tack	Medium N/25mm	FINAT FTM9

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	54 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

Designed for removable POS labels for textured surface finish homeware items.  
We always recommend pre-testing of the suitability to the substrate.

**Printing Methods**

Printable with UV letterpress, UV flexo, UV offset and gravure.  
Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
All information is subject to change without prior notice.

