

INDUSTRIAL - INDUSTRIALIssue date : 06/04/2016
Date last modification : 03/04/2018**4-IL3C-09406 - RI-440/90 ASPEN WHITE AP908 AIR FLOW WKPE160 NEUTRAL****Face Material**

Extremely conformable white gloss polymeric vinyl.

| | | |
|-------------------|---------------------------|------------|
| Type | Plasticised polymeric PVC | |
| Colour and Finish | White, Gloss | |
| Weight | 120 g/m ² ±10% | ISO-536 |
| Thickness | 90 µ ±10% | ISO 534-80 |

Adhesive

Permanent acrylic adhesive with good water, steam and temperature resistance. Not recommended for apolar surface (PE, PP). Ideal for interior decoration.

| | | |
|------------------|-------------------|------------|
| Reference | AP908 | |
| Type | Acrylic permanent | |
| Min. Appl. Temp. | +5°C | |
| Service Temp. | -40°C/+130°C | |
| Tack | 15 N/25mm | FINAT FTM9 |
| Final Adhesion | 12 N/25mm | FINAT FTM2 |
| Shear | Medium | |

Liner

| | | |
|-------------------|--|------------------|
| Type | Airflow pattern-double sided PE coated kraft paper | |
| Colour and Finish | White | |
| Weight | 160 g/m ² ±10% | PP-032 - ISO 536 |
| Thickness | 190 µ ±10% | ISO 534 |
| Transparency | n.a. % | DIN 53 147-64 |

Applications

For automotive decoration.

Printing MethodsSuitable for screenprinting.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

