

INDUSTRIAL - AUTOMOTIVE

Issue date : 22/04/2016
Date last modification : 13/12/2016**4-IL3B-08194 RI-1191/145 PVC EMBOSSED BLACK ARS6 PET100****Face Material**

Matt black embossed polymeric vinyl.

Type	Embossed polymeric vinyl	
Colour and Finish	Matt black	
Weight	194 g/m ² ±10%	ISO-536
Thickness	145 µ ±10%	ISO 534-80

Adhesive

Solvent based removable adhesive featuring low adhesion and easy and clean removability from plastics and metallic substrates.

Reference	ARS6 removable	
Type	Acrylic removable	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+100°C	
Shear	High	
Tack	Low N/inch ²	
Final Adhesion	Low N/inch	

Liner

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	140 g/m ² ±10%	PP-032 - ISO 536
Thickness	100 µ ±10%	ISO 534
Transparency	>90 %	DIN 53 147-64

Applications

For decoration and lining in the Automotive Industry.

Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

