

INDUSTRIAL - AUTOMOTIVE

Issue date : 28/10/2013
Date last modification : 02/05/2018**4-IL3B-08219 BLACK MATT WRAP 80 AP906 WKPE140 AIRFLOW****Face Material**

Matt black cast vinyl.

Type	Cast Vinyl	
Colour and Finish	Matt black	
Weight	107 g/m ² ±10%	ISO-536
Thickness	80 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring very good ultimate adhesion and excellent cohesion even at high temperatures. Not recommended on apolar substrates (like PE and PP). Also available with coloured pigments.

Reference	AP906	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+140°C	
Shear	Very high	
Tack	15 N/25mm	FINAT FTM9
Final Adhesion	7 N/25mm	FINAT FTM2

This adhesive complies with FDA 175.105.

Liner

Type	Airflow pattern-double sided PE coated kraft paper	
Colour and Finish	White	
Weight	140 g/m ² ±10%	PP-032 - ISO 536
Thickness	150 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Car-wrapping and decorative applications in automotive industry.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

