

INDUSTRIAL - INDUSTRIAL

Issue date : 20/02/2013  
Date last modification : 18/07/2017**4-IP7A-04939 - RI-21 BLACK****Liner**

Type	One side siliconised polyester
Colour and Finish	Clear
Weight	32 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	23 μ ±10% ISO 534

**Adhesive**

Black silicone based adhesive with very high cohesion even at high temperature.  
High adhesion on very low surface energy substrates.

Reference	AS1 BLACK
Type	Permanent silicone based
Min. Appl. Temp.	+10°C
Service Temp.	-20/*180°C
Shear	Very High
Tack	Medium N/inch <sup>2</sup>
Final Adhesion	High N/inch

**Applications**

Splicing tape.

**Printing Methods**

not printable

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
All information is subject to change without prior notice.

