

INDUSTRIAL - LINERLESSIssue date : 30/03/2015
Date last modification : 19/12/2017**4-IL5A-06600 RI-LAM 61 SELF WOUND ASP5A****Face Material**

Gloss silver aluminium laminated with polyester gloss clear.

Type	Aluminium/PET	
Colour and Finish	Gloss silver	
Weight	60 g/m ² ±10%	ISO-536
Thickness	35 µ ±10%	ISO 534-80

Adhesive

Solvent based permanent acrylic adhesive featuring good water and high UV resistance. Designed for overlamination and mounting applications.

Reference	ASP5A
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+120°C
Shear	Medium
Tack	Medium N/inch ²
Final Adhesion	>18 N/inch

Applications

The tape has been specifically designed for fixing the evaporator coil to the body of freezers and refrigerators.

Printing Methodsnot printable
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

