

INDUSTRIAL - INDUSTRIAL

Issue date : 08/10/2014
Date last modification : 25/08/2017**4-IL7A-08947 - RI-FOAM BLACK****Face Material**

Double sided adhesive foam.

Type	PE foam
Colour and Finish	Black
Thickness	800 μ \pm 10% ISO 534-80

Adhesive

Permanent acrylic solvent based adhesive with very good cohesion and high adhesion

Reference	AP930
Type	Acrylic permanent
Min. Appl. Temp.	+5°C
Service Temp.	-40°C/+120°C
Shear	Good
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Liner

Type	One side siliconised Glassine
Colour and Finish	White
Weight	63 g/m ² \pm 10% PP-032 - ISO 536
Thickness	55 μ \pm 10% ISO 534
Transparency	>43 % DIN 53 147-64

Applications

Fastening of automotive emblems.

Printing Methods

Not printable

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C \pm 2°C and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

