

OFFSET SHEETS - Coated Papers

Issue date : 13/07/2011
Date last modification : 12/02/2018**4-SL1B-06294 GLOSS STICKER AR804 WK85 FSC® CERTIFIED****Face Material**

Gloss white coated woodfree paper.

Type	Coated paper	
Colour and Finish	White	
Weight	80 g/m ² ±10%	ISO-536
Thickness	64 µ ±10%	ISO 534-80

Adhesive

Acrylic semi-permanent adhesive that can be removed after a short period of time after application.

Reference	AR804	
Type	Acrylic semi-permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+100°C	
Shear	High	
Tack	4 N/25mm	FINAT FTM9
Final Adhesion	5 N/25mm	FINAT FTM2

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	85 g/m ² ±10%	PP-032 - ISO 536
Thickness	87 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Album stickers which, after application, can be repositioned for a short period of time.

Printing MethodsPrintable with letterpress UV and flexo UV.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com