

ROLL LABEL - Coated Papers

Issue date : 05/01/2005  
Date last modification : 10/12/2018**4-RL1B-01792 CAST GLOSS RP1001 YG60****Face Material**

CAST Gloss white coated woodfree paper.

Type	Coated paper	
Colour and Finish	White	
Weight	80 g/m <sup>2</sup> ±10%	ISO-536
Thickness	78 µ ±10%	ISO 534-80

**Adhesive**

Rubber based permanent adhesive with high tack and adhesion on difficult and apolar (like PE and PP) substrates.

Reference	RP1001	
Type	Rubber permanent	
Min. Appl. Temp.	0°C	
Service Temp.	-20°C / +70°C	
Shear	Very High	
Tack	17 N/25mm	FINAT FTM9
Final Adhesion	10 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry &amp; moist, non fatty foodstuffs) according to the German Recommendations XIV.

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	Yellow	
Weight	58 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

Superior quality decorative and promotional labels.

**Printing Methods**

Printable with letterpress UV, flexo UV, offset UV and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

