

GRAPHICS - INK-JET DIGITAL

Issue date : 07/09/2015
Date last modification : 30/04/2018**4-GL3B-08824 RI-JET 100 GLOSS CLEAR AR802 REMOVABLE WKPE140 AIRFLOW N****Face Material**

Gloss clear monomeric vinyl film.

| | | |
|-------------------|---------------------------|------------|
| Type | Monomeric vinyl | |
| Colour and Finish | Gloss clear | |
| Weight | 134 g/m ² ±10% | ISO-536 |
| Thickness | 100 μ ±10% | ISO 534-80 |

Adhesive

Removable adhesive offering easy and clean removability from glass and from many other substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

| | |
|------------------|-----------------------|
| Reference | AR802 removable |
| Type | Acrylic removable |
| Min. Appl. Temp. | +10°C |
| Service Temp. | -40°C/+100°C |
| Shear | High |
| Tack | 4 N/inch ² |
| Final Adhesion | 3 N/inch |

Liner

| | | |
|-------------------|---------------------------------------|------------------|
| Type | Siliconised two side PE kraft airflow | |
| Colour and Finish | White | |
| Weight | 144 g/m ² ±10% | PP-032 - ISO 536 |
| Thickness | 155 μ ±10% | ISO 534 |
| Transparency | n.a. % | DIN 53 147-64 |

Applications

Glass, panels, simple surfaces can be decorated using the Airflow technology and at the same time the decorations can be removed without problems, thanks to the removable adhesive that allows to easily recover the original surface in a very short time and without traces of adhesive.

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

