

GRAPHICS - OVERLAMINATINGIssue date : 04/09/2018
Date last modification : 18/02/2019**4-GL2B-10585 RI-VISION PU 50 CLEAR GLOSS AP923 PERMANENT PET50****Face Material**

Gloss clear PU film.

Type	PU film
Colour and Finish	Gloss clear
Weight	62 g/m ² ±10% ISO-536
Thickness	50 μ ±10% ISO 534-80

Adhesive

Solvent based acrylic permanent adhesive featuring high cohesion and good water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP923
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+130°C
Shear	High
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Liner

Type	One side siliconised polyester
Colour and Finish	Clear
Weight	70 g/m ² ±10% PP-032 - ISO 536
Thickness	50 μ ±10% ISO 534
Transparency	>95 % DIN 53 147-64

Applications

For vehicle applications, for flat sided including buses, trams and taxis and for corrugated surfaces and vehicle wrapping.

Printing Methods

Printable with HP Latex technology. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

