

GRAPHICS - INK-JET DIGITAL

Issue date : Date last modification :
17/04/2019**4-GL6A-07057 PROMO RI-VIEW AR806 REMOVABLE WK135****Face Material**

Black and white perforated 40% open area soft vinyl.

Type	Perforated monomeric vinyl	
Colour and Finish	White and Black	
Weight	170 g/m ² ±10%	ISO-536
Thickness	150 µ ±10%	ISO 534-80

Adhesive

Solvent based removable adhesive featuring high water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AR806 removable
Type	Acrylic removable
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+100°C
Shear	Medium
Tack	High N/inch ²
Final Adhesion	Medium N/inch

Liner

Type	Kraft perforata laminata con PET	
Colour and Finish	White	
Weight	135 g/m ² ±10%	PP-032 - ISO 536
Thickness	150 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Outdoor and transit advertising, including p.o.p. displays and attractive window glazing. Certified by Kraffahrt-Bundesamt ABG number D 5440 dated 05.03.2008.

- . Flammability: Self - extinguish (ISO-3795)
- . Outdoor vertical exposure durability: UP TO 3 YEARS. The Durability data are given for unprinted films only and based on Zone 1 exposure conditions (Northern and Eastern Europe, Italy, France).

Printing Methods

Excellent print results with UV, solvent and eco-solvent ink-jet printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

