

ROLL LABEL - Coated Papers

Issue date : 05/01/2005  
Date last modification : 09/12/2016**4-RL1C-01766 FORMS CF AP904 WK80****Face Material**

White chemical receiving paper.

Type	Coated paper	
Colour and Finish	White	
Weight	80 g/m <sup>2</sup> ±10%	ISO-536
Thickness	90 µ ±10%	ISO 534-80

**Adhesive**

Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP).

Reference	AP904	
Type	Acrylic permanent	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+100°C	
Shear	Medium	
Tack	13 N/25mm	FINAT FTM9
Final Adhesion	11 N/25mm	FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

**Liner**

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	80 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	84 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Used in business forms, in combination with a CB coated paper when a self-adhesive copy is required.

**Printing Methods**

Suitable for different printing systems. Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

