

**GRAPHICS** - INK-JET DIGITAL

 Issue date : 03/03/2016  
 Date last modification : 24/05/2018

## 4-GL3C-10080 - RI-JET DECO WALL SANDSTONE AP940 WK135 NEUTRAL

### Face Material

White textured polymeric PVC film with a rough stone pattern.

|                   |                           |            |
|-------------------|---------------------------|------------|
| Type              | Polymeric vinyl           |            |
| Colour and Finish | Textured stone pattern    |            |
| Weight            | 215 g/m <sup>2</sup> ±10% | ISO-536    |
| Thickness         | 223 µ ±10%                | ISO 534-80 |

### Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

|                  |                       |
|------------------|-----------------------|
| Type             | Acrylic permanent     |
| Min. Appl. Temp. | +10°C                 |
| Service Temp.    | -30°C/+120°C          |
| Shear            | Very high             |
| Tack             | 6 N/inch <sup>2</sup> |
| Final Adhesion   | 9 N/inch              |

### Liner

|                   |                                        |                  |
|-------------------|----------------------------------------|------------------|
| Type              | One side siliconised clay coated Kraft |                  |
| Colour and Finish | White                                  |                  |
| Weight            | 135 g/m <sup>2</sup> ±10%              | PP-032 - ISO 536 |
| Thickness         | 145 µ ±10%                             | ISO 534          |
| Transparency      | n.a. %                                 | DIN 53 147-64    |

### Applications

For interior wall decoration.

This PVC self-adhesive material offers a cost effective solution to interior designers who are looking for a film to internal walls or shop interiors.

Application method: apply to clean, flat dust free surfaces. It is recommended to prime fresh plaster prior to application.

Product designed to give permanent bond to most wall substrates, including painted, plasterboard, primed plaster, etc.

1,5 cm overlapping recommended.

### Printing Methods

Printable with solvent, eco-solvent and UV Latex ink-jet.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

