

## 4-GL2B-06560 MONOTAPE 930P CLEAR AP901 PERMANENT/AP901 PERMANENT WKPE90

### Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP901 permanent
Type	Acrylic permanent
Min. Appl. Temp.	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	High N/inch <sup>2</sup>
Final Adhesion	Medium N/inch

### Face Material

Self-wound construction based on a clear polyester carrier.

Type	Polyester
Colour and Finish	Clear
Weight	32 g/m <sup>2</sup> ±10% ISO-536
Thickness	23 µ ±10% ISO 534-80

### Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP901 permanent
Type	Acrylic permanent
Min. Appl. Temp.	-5°C
Service Temp.	-40°C/+120°C
Shear	High
Tack	High N/inch <sup>2</sup>
Final Adhesion	Medium N/inch

### Liner

Type	Two side silicone coated two side PE coated Kraft
Colour and Finish	White
Weight	90 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	100 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

### Applications

For photographic and digital mounting.

### Printing Methods

Not printable.  
 Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.