

GRAPHICS - OVERLAMINATINGIssue date : 05/01/2005
Date last modification : 19/04/2019**4-GL3A-08109 RI-JET 30 CAST ULTRACLEAR AP923 PERMANENT PET36 MATT****Face Material**

Ultra clear gloss cast vinyl film.

Type	Soft vinyl	
Colour and Finish	Ultra gloss clear CAST	
Weight	40 g/m ² ±10%	ISO-536
Thickness	30 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent solvent based adhesive

Reference	AP923 permanent	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+130°C	
Shear	High	
Tack	Medium N/inch ²	
Final Adhesion	High N/inch	

Liner

Type	One side siliconised polyester	
Colour and Finish	Matt clear	
Weight	50 g/m ² ±10%	PP-032 - ISO 536
Thickness	36 µ ±10%	ISO 534

Applications

For overlaminating perforated graphics for where high clarity combined with conformability is required.

Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

