

Technical Data Sheet

Issue date: 14/05/2015 Date last modification: 15/04/2019

ROLL LABEL - WINE LABELS

4-RL1B-08697 LW COATED RP1003 WG74 FSC® CERTIFIED

Face Material

Coated white paper. FSC® certified.

Type Semiglossy coated

Colour and Finish White

Weight 60 g/m² \pm 10% ISO-536 Thickness 52 μ \pm 10% ISO 534

Adhesive

Rubber based permanent adhesive featuring good adhesion on slightly wet surfaces.

Reference RP1003

Type Rubber permanent

Min. Appl. Temp. 0°C

Service Temp. -20°C/+70°C Shear Very High

Tack 14 N/25mm FINAT FTM9 Final Adhesion 11 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.

Liner

Type Glassine paper

Colour and Finish White

Weight 72 g/m² ±10% PP-032 - ISO 536

Thickness 63 μ ±10% ISO 534 Transparency > 40 % DIN 53 147-64

Applications

For quality labels, with multicolour printing, with high flexibility for applications in the pharmaceutical sector. Also suitable for applications on cylindrical surfaces with reduced diameter, we recommend carrying out specific tests of the material for this type of application. NOT FOR USE IN VERY NARROW RADIUS CONTAINERS E.G. AMPOULES.

The performance of the material on non perfectly cylindrical containers must be validated for the specific product application.

REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with letterpress UV, flexo UV, offset UV, screenprinting UV and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





