

ROLL LABEL - COMMODITY

Issue date : 30/01/2016
Date last modification : 12/09/2019**4-RL1C-09265 FORMS RP3000 YG60 FSC® CERTIFIED****Face Material**

White smooth woodfree paper. FSC® certified.

Type	Smoothed paper	
Colour and Finish	White	
Weight	68 g/m ² ±10%	ISO-536
Thickness	77 µ ±10%	ISO 534

Adhesive

Rubber based permanent adhesive, general purpose for apolar and rough surfaces. RP3000 combines the rubber based propeties with high speed conversion.

Reference	RP3000	
Type	Permanent rubber based	
Min. Appl. Temp.	+ 5 °C	
Service Temp.	- 30°C/+ 80°C	
Shear	Very high	
Tack	18 N/inch ²	
Final Adhesion	8 N/inch	

Liner

Type	1 side siliconised glassine paper	
Colour and Finish	Yellow	
Weight	58 g/m ² ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534

Applications

EDP labels or VIP labels.

Printing MethodsPrintable with traditional and laser systems.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

