

ROLL LABEL - COMMODITY

Issue date : 05/01/2005  
Date last modification : 10/12/2018**4-RL1B-01878 COATED 80 AR805 YG60****Face Material**

Medium gloss white coated woodfree paper.

Type	Coated paper	
Colour and Finish	White	
Weight	80 g/m <sup>2</sup> ±10%	ISO-536
Thickness	65 µ ±10%	ISO 534-80

**Adhesive**

Acrylic removable adhesive for general purpose applications on a wide variety of substrates.

Reference	AR805	
Type	Acrylic removable	
Min. Appl. Temp.	+5°C	
Service Temp.	-15°C/+100°C	
Shear	Medium	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

**Liner**

Type	One side siliconised Glassine	
Colour and Finish	Yellow	
Weight	58 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	51 µ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

**Applications**

high quality labels for industrial and promotional use, when good removability is needed.

**Printing Methods**

Printable with UV letterpress, UV flexo, UV offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

